



Hathorn® camera reels are designed to work with any Hathorn control module, past present or future. These rugged and durable camera reels come fitted with your choice of Hathorn self-levelling camera heads, all equipped with super-bright, cool running LEDs for optimal picture quality.

Butt-welded steel frame construction, stainless steel camera heads and your choice of cable size allow you to push further than ever before and remain in the field longer with Hathorn's legendary reliability.

Hathorn camera reels are trusted by plumbers, municipalities, general contractors, home inspectors, petrochemical companies, and mining engineers to deliver a clear, recordable video inspection every time the camera is used. Designed and manufactured in North America, with a full one-year warranty.



For use with Hathorn Command Modules



Self-Levelling Camera Heads



200 ft to 600 ft of Push Rod



512Hz or 640Hz High Power Sonde



Industry-Leading Warranty

PROUDLY DESIGNED AND MANUFACTURED IN NORTH AMERICA



SPECIFICATIONS

Display

Size & Display: Compatible with all Hathorn control modules. H12+ recommended for best picture and options

Features

Sonde Frequency: High power 512Hz or 640Hz (available only with H12+ controller)

Push Rod: HDPE push rod with coax core - multiple lengths and thicknesses

Weight & Dimensions

Weight: See specific item in list to the right

Dimensions (L x W x H): See specific item in list to the right

Weight & Dimensions

Water Resistance - Camera & Rod: IP67 to 60psi

Water Resistance - Battery Cradle: IP65

Water Resistance - Reel Hub: IP64

Operating Temperature: 14°F to 122°F (-10°C to 50°C)

Storage Temperature: 4°F to 140°F (-20°C to 60°C)



Extra Large

Catalog #	Camera Head	Self Leveling	Rod Length	Rod Size	Min. 90° Elbow	Weight	Max Pipe	Dimensions
XLR-5568-SL	1.68"	✓	500 ft.	5/8"	3"	90lbs.	12"	33" x 29" x 16"
XLR-5168-SL	1.68"	✓	500 ft.	1/2"	3"	75lbs.	12"	33" x 29" x 16"

Large

Catalog #	Camera Head	Self Leveling	Rod Length	Rod Size	Min. 90° Elbow	Weight	Max Pipe	Dimensions
LR-4168-SL	1.68"	✓	400 ft.	1/2"	3"	65 lbs.	12"	33" x 29" x 16"
LR-3168-SL	1.68"	✓	300 ft.	1/2"	3"	55 lbs.	12"	33" x 29" x 16"
LR-2168-SL	1.68"	✓	200 ft.	1/2"	3"	45 lbs.	12"	33" x 29" x 16"
LR-4143-SL	1.43"	✓	400 ft.	1/2"	3"	65 lbs.	10"	33" x 29" x 16"
LR-3143-SL	1.43"	✓	300 ft.	1/2"	3"	55 lbs.	10"	33" x 29" x 16"
LR-2143-SL	1.43"	✓	200 ft.	1/2"	3"	45 lbs.	10"	33" x 29" x 16"

Mid

Catalog #	Camera Head	Self Leveling	Rod Length	Rod Size	Min. 90° Elbow	Weight	Max Pipe	Dimensions
MR-2168-SL	1.68"	✓	200 ft.	1/2"	3"	42 lbs.	12"	29" x 18" x 15"
MR-2143-SL	1.43"	✓	200 ft.	1/2"	3"	42 lbs.	10"	29" x 18" x 15"
MR-2123-SL	1.23"	✓	200 ft.	0.400"	2"	42 lbs.	6"	29" x 18" x 15"

Mini

Catalog #	Camera Head	Self Leveling	Rod Length	Rod Size	Min. 90° Elbow	Weight	Max Pipe	Dimensions
MN-2123-SL	1.23"	✓	200 ft.	3/8"	2"	33 lbs.	6"	24" x 18" x 10"
MN-2100	1"	✗	200 ft.	3/8"	2"	33 lbs.	4"	24" x 18" x 10"

*Straight View Cameras Available



PROUDLY DESIGNED AND MANUFACTURED IN NORTH AMERICA

HATHORNCORP.COM | SALES@HATHORNCORP.COM
 North America: 1-866-HATHORN | International: 1-905-604-7040

GET A QUOTE

