



Hathorn® Wi-Fi camera reels offer the convenience of streaming video inspections directly to two Apple or Android mobile devices at the same time using our free Hathorn app. Allows the user to take screen shots, record videos and make voice commentary. Save videos to your phone, email to your clients or attach to your route management software seamlessly.

All Hathorn cameras are portable and can be powered by external 18V Milwaukee® or equivalent batteries (not included) offering over 12 hours of run time on a single 3.0Ah battery. Batteries are inserted into the near indestructible Hathorn hub. No wires, no external battery cradles, just solid North American engineering.

All Wi-Fi reels feature a footage counter and a 512Hz sonde. Like all Hathorn products, they are genuinely North American made with a butt-welded steel frame construction and made with industry-leading HDPE premium cables.



Screen Shot
Function



Wi-Fi Reel for use
with Phone or
Tablet



Stream & Record to
Mobile Device



Works with 18V
Milwaukee or
Equivalent
Batteries



200 ft to 400 ft of
Push Rod



512Hz High Power
Sonde



Over 12 hrs of
Runtime on a
Single Charge



Self-Levelling
Camera Heads



Industry-
Leading
Warranty

PROUDLY DESIGNED AND MANUFACTURED IN NORTH AMERICA

HATHORNCORP.COM | SALES@HATHORNCORP.COM

North America: 1-866-HATHORN | International: 1-905-604-7040

GET A QUOTE



SPECIFICATIONS

Display

Size & Type Dependent upon Apple/Android Device

Recording, Storage & Features

Recording Options MPEG4

Screen Shot JPEG

File Storage Mobile Device, cloud or USB

Footage Counter Feet or meters - resettable

Sonde Frequency 512Hz

Push Rod HDPE - 200 ft to 400 ft / 3/8" to 5/8"

Start Up Time ~ 15 seconds

Power

Battery (not incl.) Only Milwaukee® M18 18V or equivalent

Battery Life ~ 12Hrs. using 3.0Ah

AC/DC Adapter 12V - 4.1A (included)

Environmental

Water Resistance - Camera & Rod IP68 to 60psi

Water Resistance - Reel Hub IP65

Operating Temperature 14°F to 122°F (-10°C to 50°C)

Storage Temperature -4°F to 140°F (-20°C to 60°C)

Wi-Fi Frequency IEEE802.11b/g/n



Large

Catalog	Camera Head	Self Leveling	Rod Length	Rod Size	Min. 90° Elbow	Weight	Max Pipe	Dimensions
WLR-4168-SL	1.68"	✓	400 ft.	1/2"	3"	65 lbs.	12"	33" x 29" x 16"
WLR-3168-SL	1.68"	✓	300 ft.	1/2"	3"	55 lbs.	12"	33" x 29" x 16"
WLR-2168-SL	1.68"	✓	200 ft.	1/2"	3"	45 lbs.	12"	33" x 29" x 16"
WLR-4143-SL	1.43"	✓	400 ft.	1/2"	3"	65 lbs.	10"	33" x 29" x 16"
WLR-3143-SL	1.43"	✓	300 ft.	1/2"	3"	55 lbs.	10"	33" x 29" x 16"
WLR-2143-SL	1.43"	✓	200 ft.	1/2"	3"	45 lbs.	10"	33" x 29" x 16"

Mid

Catalog	Camera Head	Self Leveling	Rod Length	Rod Size	Min. 90° Elbow	Weight	Max Pipe	Dimensions
WMR-2168-SL	1.68"	✓	200 ft.	1/2"	3"	42 lbs.	12"	29" x 18" x 15"
WMR-2143-SL	1.43"	✓	200 ft.	1/2"	3"	42 lbs.	10"	29" x 18" x 15"
WMR-2123-SL	1.23"	✓	200 ft.	0.400"	2"	42 lbs.	6"	29" x 18" x 15"

Mini

Catalog	Camera Head	Self Leveling	Rod Length	Rod Size	Min. 90° Elbow	Weight	Max Pipe	Dimensions
WMN-2123-SL	1.23"	✓	200 ft.	3/8"	2"	33 lbs.	6"	24" x 18" x 10"
WMN-2100	1	✗	200 ft.	3/8"	1.5"	33 lbs.	4"	24" x 18" x 10"

*Straight View Cameras Available

PROUDLY DESIGNED AND MANUFACTURED IN NORTH AMERICA

HATHORNCORP.COM | SALES@HATHORNCORP.COM

North America: 1-866-HATHORN | International: 1-905-604-7040

GET A QUOTE

