



HATHORN
INSPECTION CAMERAS

M2 INSPECTION CAMERA SYSTEM

Proudly designed and manufactured in North America
Powered by a Milwaukee™ 18V or compatible external battery



Hathorn M2 systems come standard with a 7.4" shatter resistant LCD monitor and are compatible with 18V Milwaukee™ batteries for ultimate portability and over 5 hours of runtime on a single charge. All M2s come equipped with 100ft. of premium cable and your choice of Straight-View DuraCAM™ camera heads, all with cool running super bright LED lights. Trusted by plumbers and contractors all over North America to deliver rugged dependability and portability. Designed and manufactured in North America, with a full one-year warranty. The M2 offers a municipal grade product quality with an industry leading feature set.

Upgrade to DuraCAM™!

M2 FEATURES

- 7.4" Impact resistant screen
- External 18V battery compatibility
- 512hz sonde control
- Available with Wi-Fi PipeSTREAM™ stream/record
- Straight view DuraCAM™ camera heads



HATHORN

North America: 1-866-HATHORN
International: +1-905-604-7040
www.hathorncorp.com • info@hathorncorp.com

M2 INSPECTION CAMERA SYSTEM

Specifications




- DuraCAM™ Straight-View camera heads with HD picture quality and auto-iris technology
- 1.23" - 12 cool running LEDs - 12k LUX @ 6"
- 1.43" - 16 cool running LEDs - 16k LUX @ 6"
- 1.68" - 20 cool running LEDs - 20k LUX @ 6"
- Choice of premium push-rod with HDPE jacket
- Sonde - 512 Hz High-power
- Operating Temperature – -30C to 60C (-22F to 140F)
- Ingress Protection of Reel & Camera Head – IPx5 to 60PSI
- Optional Wi-Fi PipeSTREAM™ stream/record (App for Apple or Android)
- Powered by 18V Milwaukee™ or compatible batteries or 12V AC/DC adapter
- Cool running, high intensity LEDs for longer camera life
- Dimensions - 84cm x 48cm x 41cm / 33" x 19" x 16"
- Weight -16kg / 35lbs

Catalog #	Camera Head	Self Leveling	Rod length	Rod Size	Min 90 Elbow	Max. Pipe well Lit
M2W-1168	1.68"	No	100 ft.	1/2"	3"	12"
M2-1168	1.68"	No	100 ft.	1/2"	3"	12"
M2W-1143	1.43"	No	100 ft.	0.400"	3"	10"
M2-1143	1.43"	No	100 ft.	0.400"	3"	10"

Accessories

Catalog #	Description
10108 / 10140	regular skid for 1.68" / 1.43"
10137 / 10123	regular skid for 1.23" self leveling / 1.23" straight view
10109	3" grooved skid for 1.68" cameras
10160	3" grooved skid for 1.43" self leveling cameras
10187	P- trap skid for 1.43" cameras
10162 / 10161	roller skid for up to 12" pipe (1.68" / 1.43")



Find more information at our website - www.hathorncorp.com



Wi-Fi App available at:



HATHORN

North America: 1-866-HATHORN
 International: +1-905-604-7040
www.hathorncorp.com • info@hathorncorp.com

M7 INSPECTION CAMERA SYSTEM

Proudly designed and manufactured in North America
Powered by a Milwaukee™ 18V or compatible external battery



Record to
USB Drive



Wi-Fi
Available

Hathorn M7 systems come standard with a 7.4" shatter resistant LCD monitor and are compatible with 18V Milwaukee™ batteries for ultimate portability and over 4 hours of runtime on a single charge. All M7s come equipped with 200ft. of premium cable and your choice of **DuraCAM™** camera heads, all with cool running super bright LED lights. Trusted by plumbers and contractors all over North America to deliver rugged dependability and portability. Designed and manufactured in North America, with a full one-year warranty. The M7 offers a municipal grade product quality with an industry leading feature set.

Upgrade to DuraCAM™!

M7 FEATURES

- 7.4" Impact resistant screen
- Self leveling camera heads standard
- Straight view camera heads available
- USB Recording
- One touch recording and video pause
- Adjustable camera lighting
- Onscreen footage counter
- External 18V battery compatibility
- 512hz sonde control
- Available with Wi-Fi PipeSTREAM™ stream/record



HATHORN

North America: 1-866-HATHORN

International: +1-905-604-7040

www.hathorncorp.com • info@hathorncorp.com

M7 INSPECTION CAMERA SYSTEM

Specifications

- DuraCAM™ self leveling or straight view camera heads with HD picture quality and auto-iris technology
- 1.23" - 12 dimmable cool running LEDs - 12k LUX @ 6"
- 1.43" - 16 dimmable cool running LEDs - 16k LUX @ 6"
- 1.68" - 20 dimmable cool running LEDs - 20k LUX @ 6"
- Choice of premium push-rod with HDPE jacket
- Sonde - 512 Hz High-power
- Operating Temperature – -30C to 60C (-22F to 140F)
- Optional Wi-Fi PipeSTREAM™ stream/record (App for Apple or Android)
- Powered by 18V Milwaukee™ or compatible batteries or 12V AC/DC adapter
- Ingress Protection of Reel & Camera Head – IPx5 to 60PSI
- Dimensions - 84cm x 48cm x 41cm / 33" x 19" x 16"
- Weight - 20kg / 45lbs



Catalog #	Camera Head	Self Leveling	Rod Length	Rod Size	Min. 90° Elbow	Max. Pipe Well Lit
M7W-2168-SL / M7W-2168	1.68"	Avail.	200ft.	1/2"	3"	12"
M7-2168-SL / M7-2168	1.68"	Avail.	200ft.	1/2"	3"	12"
M7W-2143-SL / M7W-2143	1.43"	Avail.	200ft.	1/2"	3"	10"
M7-2143-SL / M7-2143	1.43"	Avail.	200ft.	1/2" or 0.400"	3"	10"
M7W-2123-SL / M7W-2123	1.23"	Avail.	200ft.	3/8"	2"	6"
M7-2123-SL / M7-2123	1.23"	Avail.	200ft.	3/8" or 0.400"	2"	6"

Accessories

Catalog #	Description
10108 / 10140	regular skid for 1.68" / 1.43"
10137 / 10123	regular skid for 1.23" self leveling / 1.23" straight view
10109	3" grooved skid for 1.68" cameras
10160	3" grooved skid for 1.43" self leveling cameras
10187	P- trap skid for 1.43" cameras
10162 / 10161	roller skid for up to 12" pipe (1.68" / 1.43")

Find more information at our website - www.hathorncorp.com



Wi-Fi App available at:



North America: 1-866-HATHORN
 International: +1-905-604-7040
www.hathorncorp.com • info@hathorncorp.com

H12i CONTROL MODULE

Proudly designed and manufactured in North America
Powered by an internal lithium battery



Record to
USB Drive



Wi-Fi
Available



Super Bright
Daylight Readable

The Hathorn H12i Control Module is equipped with a 12.1" **VividHD** LCD screen with almost twice the brightness of the leading brand, making it the largest and best daylight readable monitor in the industry. The M12 is the pro's choice for any light condition (including direct sunshine), providing stunning HD picture quality, high contrast and 8X digital "pan & zoom" technology revealing details missed by other lateral push cameras. Whether you are working in brutal Canadian winters or hot Arizona summers it's time to...

Upgrade to VividHD!

H12i FEATURES

- 12.1" **VividHD** LCD screen that is daylight readable and impact resistant
- Internal 2 hour lithium battery
- One touch USB recording, video pause, and playback
- Available with Wi-Fi **PipeSTREAM™** stream/record
- Adjustable camera head lighting
- Component video/audio output
- 8 pages of on-screen text writing
- On-screen footage counter with reset
- Full sized keyboard
- 512hz sonde control
- Genuinely North American made



HATHORN

North America: 1-866-HATHORN
International: +1-905-604-7040
www.hathorncorp.com • info@hathorncorp.com

H12i CONTROL MODULE



Specifications

- VividHD 12.1" LCD – Daylight readable, impact resistant, industry leading HD picture quality with up to 8X digital zoom
- Video Recording – MPEG4 – RCA out, USB or Wi-Fi PipeSTREAM™ stream/record (App for Apple or Android)
- Lighting – Dimmable camera head lighting control
- Audio – Integrated microphone and speaker
- USB – 1 x 0.5A port USB 2.0
- Operating Temperature – -30C to 60C (-22F to 140F)
- Machined military grade aluminum connectors and face plate
- 12V AC/DC adapter or internal 2hr Li-Ion battery
- Dimensions - 40cm x 30cm x 18cm / 16" x 12" x 7"
- Weight - 6.5kg / 14lbs

Catalog#	Reel Compatibility	Wi-Fi Streaming/Recording	Digital Zoom	Power	Screen
H12i	All Hathorn except Wi-Fi reels. RIDGID reels without Tilt-Sense™	No	1X, 2X, 3X, 4X and 8X	12V AC/DC Adapter (included) or Internal 2hr. Li-Ion rechargeable	1000cd/m2 (nits)
H12i-W		Yes			
H12i-GS	All Hathorn except Wi-Fi reels. All GL, G2 and G3 General Wire reels, Gator Cams and Ratech.	No			
H12i-GS-W		Yes			


Accessories

Catalog #	Description
10100	For connecting H12i controllers to all Hathorn Micron, Mini, Mid and Large Reels
80124	Patch Cable from Hathorn Controller to GL Reel and Ratech*
80129	Patch Cable from Hathorn Controller to G3 Reel*
80130	Patch Cable from Hathorn Controller (Silver / Silver Connectors) to G2 Reel*
80131	Patch Cable from Hathorn Controller (Black / Silver Connectors) to G2 Reel*


*Available while supplies last



Find more information at our website - www.hathorncorp.com



Wi-Fi App available at:



North America: 1-866-HATHORN
 International: +1-905-604-7040
www.hathorncorp.com • info@hathorncorp.com

H12 CONTROL MODULE

Proudly designed and manufactured in North America
Compatible with Milwaukee™ 18V or equivalent batteries



Record to
USB Drive



Wi-Fi
Available



Super Bright
Daylight Readable

The Hathorn H12 Control Module is equipped with a 12.1" **VividHD** LCD screen with almost twice the brightness of the leading brand, making it the largest and best daylight readable monitor in the industry. The M18 is the pro's choice for any light condition (including direct sunshine), providing stunning HD picture quality, high contrast and 8X digital "pan & zoom" technology revealing details missed by other lateral push cameras. Whether you are working in brutal Canadian winters or hot Arizona summers it's time to...

Upgrade to VividHD!

H12 FEATURES

- 12.1" **VividHD** LCD screen that is daylight readable and impact resistant
- Compatible with Milwaukee™ 18V or equivalent batteries for portability and extended run time
- One touch USB recording, video pause, and playback
- Available with Wi-Fi **PipeSTREAM™** stream/record
- Adjustable camera head lighting
- Component video/audio output
- 8 pages of on-screen text writing
- Onscreen footage counter with reset
- Full sized keyboard
- 512hz sonde control
- Genuinely North American made



HATHORN

North America: 1-866-HATHORN
International: +1-905-604-7040
www.hathorncorp.com • info@hathorncorp.com

H12 CONTROL MODULE



Specifications

- VividHD 12.1" LCD – Daylight readable, impact resistant, industry leading HD picture quality with up to 8X digital zoom
- Video Recording – MPEG4 – RCA out, USB or Wi-Fi PipeSTREAM™ stream/record (App for Apple or Android)
- Lighting – Dimmable camera head lighting control
- Audio – Integrated microphone and speaker
- USB – 1 x 0.5A port USB 2.0
- Operating Temperature – -30C to 60C (-22F to 140F)
- Machined military grade aluminum connectors and face plate
- Power Source – 12V AC/DC adapter or external 18V battery (not included)
- Dimensions - 40cm x 30cm x 18cm / 16" x 12" x 7"
- Weight - 6.5kg / 14lbs

Catalog#	Reel Compatibility	Wi-Fi Streaming/Recording	Digital Zoom	Power	Screen
H12	All Hathorn except Wi-Fi reels. RIDGID reels without Tilt-Sense™	No	1X, 2X, 3X, 4X and 8X	12 VAC/DC Adapter (included) or External Milwaukee 18V Compatible - Battery Sold Separately	1000cd/m2 (nits)
H12-W		Yes			
H12-GS	All Hathorn except Wi-Fi reels. All GL, G2 and G3 General Wire reels, Gator Cams and Ratech. -	No			
H12-GS-W		Yes			


Accessories

Catalog #	Description
10100	For connecting H12 controllers to all Hathorn Micron, Mini, Mid and Large Reels
80124	Patch Cable from Hathorn Controller to GL Reel and Ratech*
80129	Patch Cable from Hathorn Controller to G3 Reel*
80130	Patch Cable from Hathorn Controller (Silver / Silver Connectors) to G2 Reel*
80131	Patch Cable from Hathorn Controller (Black / Silver Connectors) to G2 Reel*


*Available while supplies last



Find more information at our website - www.hathorncorp.com



Wi-Fi App available at:



HATHORN

North America: 1-866-HATHORN
 International: +1-905-604-7040
www.hathorncorp.com • info@hathorncorp.com

DuraSCOPE™

MICRON CAMERA REELS

Proudly Designed and Manufactured in North America



Micron Reel for
use with VividHD
Command Modules

Micron Wi-Fi Reel
for use with phone
or tablet

Upgrade to DuraSCOPE™!

Micron DuraSCOPE™ camera reels can be used with any Hathorn control module or used with your own mobile Apple/Android device, if you choose the Wi-Fi PipeSTREAM™ stream/record option. The Wi-Fi option is a standalone camera system that allows live streaming and recording to up to four devices at the same time.

DuraSCOPE™ Micron reels are trusted by plumbers, general contractors, and home inspectors to deliver high definition, recordable video inspections. These municipal grade reels offer butt-welded steel frame construction and premium 1/4" cable allowing you to push further in a small diameter pipe. Hathorn DuraSCOPE™ reels come equipped with your choice of DuraCAM™ 1" or 7/8" straight view camera heads, allowing you to inspect pipes from 1" to 4" with ease. DuraCAM™ heads are also equipped with super bright, cool running LEDs for optimal HD picture quality.

Micron reels are only 16" tall and weigh under 16 lbs. The Wi-Fi option is powered by an external Milwaukee™ 18V or compatible battery, which can last up to 6 hours. These features give Micron reels the ultimate in portability and allow you to stay in the field longer.



North America: 1-866-HATHORN
International: +1-905-604-7040
www.hathorncorp.com • info@hathorncorp.com

DuraSCOPE™

MICRON CAMERA REELS



Micron Camera Reel used with an M18 Command Module.



WI-FI OPTION SPECIFICATIONS

- Compatibility – Wi-Fi PipeSTREAM™ stream/record (App for Apple or Android)
- Power – 18V Milwaukee™ battery or equivalent or included AC/DC adapter
- Camera Heads - DuraCAM™ straight view camera heads with HD picture quality and auto-iris technology
- Non-Dimmable Lighting – 8 super bright cool running LEDs for long camera life ~8,000 LUX at 6"
- Push Rod – with premium 1/4" rod with HDPE jacket
- Sonde - 512 Hz High-power sonde
- Operating Temperature – -30C to 60C (-22F to 140F)
- Ingress Protection of Reel & Camera Head – IPx5 to 60PSI

NON-WI-FI OPTION SPECIFICATIONS

- Compatibility – All Hathorn M10, M12 & M18 controllers
- Power – Powered using Hathorn control module
- Camera Heads - DuraCAM™ straight view camera heads with HD picture quality and auto-iris technology
- Dimmable Lighting – 8 super bright cool running LEDs for long camera life ~8,000 LUX at 6"
- Push Rod – with premium 1/4" rod with HDPE jacket
- Sonde - 512 Hz High-power sonde
- Operating Temperature – -30C to 60C (-22F to 140F)
- Ingress Protection of Reel & Camera Head – IPx5 to 60PSI

	Catalog #	Wi-Fi	Camera Head	Self Leveling	Rod Length	Rod Size	Min 90° Elbow	Max. Pipe Well Lit	LBS.	Dimensions
Micron	MC-1100	No	1"	No	100ft.	1/4"	1.5"	4"	15lbs	16"x12"x10"
	MC-1078	No	7/8"	No	100ft.	1/4"	1.5"	4"		
	WMC-1100	Yes	1"	No	100ft.	1/4"	1.5"	4"	16lbs	
	WMC-1078	Yes	7/8"	No	100ft.	1/4"	1.5"	4"		

* Camera head skirts are included and always recommended to protect camera heads. Find these accessories and spare parts at our website - www.hathorncorp.com



Wi-Fi App available at:



North America: 1-866-HATHORN
 International: +1-905-604-7040
www.hathorncorp.com • info@hathorncorp.com

DuraSCOPE™

CAMERA REELS

Proudly Designed and Manufactured in North America



Mini Reel



Mid Reel



Large Reel

Upgrade to DuraSCOPE™!

Hathorn DuraSCOPE™ camera reels are designed to work with any Hathorn control module, past, present or future. These municipal grade camera reels come fitted with your choice of DuraCAM™ self-leveling or straight view camera heads all equipped with super bright cool running LEDs for optimal HD picture quality. But welded steel frame construction, stainless steel camera heads and your choice of cable size allow you to push further than ever before and remain in the field longer with Hathorn's legendary reliability. Hathorn DuraSCOPE™ camera reels are trusted by plumbers, municipalities, general contractors, home inspectors, petrochemical companies, and mining engineers to deliver a high definition, recordable video inspection every time the camera is used.

Features

- Compatible with all Hathorn control modules
- Self-Leveling camera heads standard
- Straight View camera heads available
- Footage counter equipped
- 512hz sonde
- Industry leading HDPE premium cables



HATHORN

North America: 1-866-HATHORN
International: +1-905-604-7040
www.hathorncorp.com • info@hathorncorp.com

DuraSCOPE™ CAMERA REELS

SPECIFICATIONS

- Compatibility – All Hathorn M10, M12 & M18 controllers
- Powered using Hathorn control modules
- DuraCAM™ self leveling or straight view camera heads with HD picture quality and auto-iris technology
- 1.00" - 8 dimmable cool running LEDs - 8k LUX @ 6"
- 1.23" - 12 dimmable cool running LEDs - 12k LUX @ 6"
- 1.43" - 16 dimmable cool running LEDs - 16k LUX @ 6"
- 1.68" - 20 dimmable cool running LEDs - 20k LUX @ 6"
- Choice of premium push-rod with HDPE jacket
- Sonde - 512 Hz High-power
- Operating Temperature – -30C to 60C (-22F to 140F)
- Ingress Protection of Reel & Camera Head – IPx5 to 60PSI



	Catalog#	Camera Head	Self Leveling	Rod Length	Rod Size	Min 90° Elbow	Max. Pipe Well Lit	LBS.	Dimensions
Extra Large	XLR-5568 / XLR-5568-SL	1.68"	Avail	500ft.	5/8"	3"	12"	90lbs.	33"x19"x16"
	XLR-5168 / XLR-5168-SL	1.68"	Avail	500ft	1/2"	3"	12"	75lbs.	
Large	LR-4168-SL / LR-4168	1.68"	Avail.	400ft.	1/2"	3"	12"	65lbs.	33"x19"x16"
	LR-3168-SL / LR-3168	1.68"	Avail.	300ft.	1/2"	3"	12"	55lbs.	
	LR-2168-SL / LR-2168	1.68"	Avail.	200ft.	1/2"	3"	12"	45lbs.	
	LR-4143-SL / LR-4143	1.43"	Avail.	400.ft	1/2"	3"	10"	65lbs.	
	LR-3143-SL / LR-3143	1.43"	Avail.	300.ft	1/2"	3"	10"	55lbs.	
	LR-2143-SL / LR-2143	1.43"	Avail.	200.ft	1/2"	3"	10"	45lbs.	
Mid	MR-2168-SL / MR-2168	1.68"	Avail.	200ft.	1/2"	3"	12"	42lbs.	29"x18"x15"
	MR-2143-SL / MR-2143	1.43"	Avail.	200ft	0.400"	3"	10"		
	MR-2123-SL / MR-2123	1.23"	Avail.	200ft.	0.400"	2"	6"		
Mini	MN-2135	1.35"	No	200ft.	3/8"	1.5"	6"	33lbs.	24"x18"x10"
	MN-2123-SL / MN-2123	1.23"	Avail.	200ft.	3/8"	2"	6"		
	MN-2100	1"	No	200ft.	3/8"	1.5"	4"		

* Skids are always recommended to protect camera head. Roller skids are recommended options for pipes larger than 8"
Find these accessories and spare parts at our website - www.hathorncorp.com



Wi-Fi App available at:



North America: 1-866-HATHORN
International: +1-905-604-7040
www.hathorncorp.com • info@hathorncorp.com

DuraSCOPE™

WIFI CAMERA REELS

Proudly Designed and Manufactured in North America



Mini Wi-Fi Reel



Mid Wi-Fi Reel



Large Wi-Fi Reel

Upgrade to DuraSCOPE™!

Hathorn Wi-Fi DuraSCOPE™ reels are designed to work with Wi-Fi PipeSTREAM™ stream/record, using an app for Apple or Android. Stream video inspections directly to your mobile device; record, screen shot, make voice commentary and share video inspections seamlessly. All of these municipal grade Wi-Fi reels are compatible with 18V Milwaukee™ or equivalent batteries for the ultimate in portability. Each reel is fitted with your choice of DuraCAM™ self-leveling or straight view camera heads, all equipped with super bright cool running LEDs, for optimal HD picture quality. Butt welded steel frame construction, stainless steel camera heads, your choice of cable size, and Hathorn's legendary reliability allow you to push further than ever before and remain in the field longer. Hathorn Wi-Fi DuraSCOPE™ camera reels are trusted by plumbers, municipalities, general contractors, home inspectors, petrochemical companies, and mining engineers to deliver a high definition, recordable video inspection every time the camera is used.

Features

- Wi-Fi PipeSTREAM™ stream/record
- Self-Leveling camera heads standard
- Straight View camera heads available
- On-screen footage counter
- 512hz sonde control and reset
- External 18V battery compatibility
- Industry leading HDPE premium cables



HATHORN

North America: 1-866-HATHORN
International: +1-905-604-7040
www.hathorncorp.com • info@hathorncorp.com

DuraSCOPE™

WI-FI CAMERA REELS

SPECIFICATIONS

- Compatibility – Wi-Fi PipeSTREAM™ stream/record, an app for all Apple or Android portable devices
- Powered by external Milwaukee™ or comp.18V batteries.
- DuraCAM™ self-leveling or straight view camera heads with HD picture quality and auto-iris technology
- 1.00" - 8 cool running LEDs - 8k LUX @ 6"
- 1.23" - 12 cool running LEDs - 12k LUX @ 6"
- 1.43" - 16 cool running LEDs - 16k LUX @ 6"
- 1.68" - 20 cool running LEDs - 20k LUX @ 6"
- Choice of premium push-rod with HDPE jacket
- Sonde - 512 Hz High-power
- Operating Temperature – -30C to 60C (-22F to 140F)
- Ingress Protection of Reel & Camera Head – IPx5 to 60PSI

Actual screen shot taken on an iPad from a mini camera in a 3" pipe.



	Catalog#	Camera Head	Self Leveling	Rod Length	Rod Size	Min 90° Elbow	Max. Pipe Well Lit	LBS.	Dimensions
Large	WLR-4168-SL / WLR-4168	1.68"	Avail.	400ft.	1/2"	3"	12"	65lbs.	33"x19"x16"
	WLR-3168-SL / WLR-3168	1.68"	Avail.	300ft.	1/2"	3"	12"	55lbs.	
	WLR-2168-SL / WLR-2168	1.68"	Avail.	200ft.	1/2"	3"	12"	45lbs.	
	WLR-4143-SL / WLR-4143	1.43"	Avail.	400.ft	1/2"	3"	10"	65lbs.	
	WLR-3143-SL / WLR-3143	1.43"	Avail.	300.ft	1/2"	3"	10"	55lbs.	
	WLR-2143-SL / WLR-2143	1.43"	Avail.	200.ft	1/2"	3"	10"	45lbs.	
Mid	WMR-2168-SL / WMR-2168	1.68"	Avail.	200ft.	1/2"	3"	12"	42lbs.	29"x18"x15"
	WMR-2143-SL / WMR-2143	1.43"	Avail.	200.ft	0.400"	3"	10"		
	WMR-2123-SL / WMR-2123	1.23"	Avail.	200ft.	0.400"	2"	6"		
Mini	WMN-2135	1.35"	No	200ft.	3/8"	1.5"	6"	33lbs.	24"x18"x10"
	WMN-2123-SL / WMN-2123	1.23"	Avail.	200ft.	3/8"	2"	6"		
	WMN-2100	1"	No	200ft.	3/8"	1.5"	4"		

* Camera head skids are included and always recommended to protect camera heads. Roller skids are recommended options for pipes larger than 8". Find these accessories and spare parts at our website - www.hathorncorp.com



WiFi App available at:



North America: 1-866-HATHORN
 International: +1-905-604-7040
www.hathorncorp.com • info@hathorncorp.com

KEYHOLE GAS LINE

Proudly North American designed and built
Designed for use with Keyhole Pipe Entry systems

CAMERA SYSTEM




Not
Rated as
Intrinsically
Safe or
Explosion
Proof



240GB SSD



Super Bright
Daylight
Readable



Record to
USB Drive

Hathorn's gas camera system was specially developed in partnership with the Gas Technology Institute in Chicago. The system and specialty camera head were designed to provide America's utilities a way to inspect live gas mains through 90 degree keyhole pipe entries using stuffing boxes and traditional gas line insertion tools. Though not rated as intrinsically safe or explosion proof, Hathorn's gas cameras have been the go-to camera in the industry for over a decade providing users the ability to inspect 2-6" gas mains while recording inspections to USB or HDD. The 12.1" monitor is the pro's choice for any light condition (including direct sunshine), providing stunning HD picture quality, high contrast and 8X digital "pan & zoom" technology revealing details otherwise missed by other gas cameras. Whether you are working in brutal Canadian winters or hot Arizona summers it's time to...

Upgrade to VividHD!

FEATURES

- 12.1" **VividHD** daylight readable monitor
- Record to USB or internal 240GB SSD
- Transfer data via USB cable to computer
- Built-in microphone and speaker
- Play, pause, record and 8x zoom
- MPEG4 recording files
- 8 pages of text writing with memory saves
- On-screen footage counter
- Adjustable lighting controls
- 512Hz Sonde
- Internal Li-Ion 4hr battery with built-in charger
- 1.35" straight view gas camera head for use on 2" elbows & saddle joints, in up to 6" pipes



HATHORN

North America: 1-866-HATHORN

International: +1-905-604-7040

www.hathorncorp.com • info@hathorncorp.com

KEYHOLE GAS LINE

CAMERA SYSTEM



Specifications

- VividHD 12.1" LCD – Industry leading HD picture quality with up to 8X digital zoom, impact resistant, with industry leading brightness
- Lighting – 12 dimmable cool running LEDs - 12k LUX @ 6"
- Video Recording – MPEG4 – RCA out, USB or 240GB HDD
- Audio – Integrated microphone and speaker
- USB – 2 x 0.5A port USB 2.0
- Operating Temperature – -30C to 60C (-22F to 140F)
- Machined military grade aluminum connectors and face plate
- 12V AC/DC adapter or internal 4hr Li-Ion battery
- Ingress Protection of Reel & Camera Head – IPx5 to 60PSI
- Sonde - 512 Hz High-power

Controller Catalog #	Reel Compatibility	Digital Zoom	Power	Screen	Dimensions	Weight
KGC-12	Only Hathorn Gas Reels and Cameras	1X, 2X, 3X, 4X and 8X	12V AC/DC Adapter (included) or Internal 4hr. Li-Ion rechargeable	1000cd/m2 (nits)	40x30x18cm 16x12x7 inches	10kg / 22lbs

Reel Catalog #	Camera Head	Rod length	Rod Size	Min. 90° Elbow	Max. Pipe Well Lit	Weight	Dimensions
KGR - 400	1.35"	400ft.	3/8"	2"	6"	55lbs.	33"x19"x16"
KGR - 200	1.35"	200ft.	3/8"	2"	6"	45lbs	33"x19"x16"

Accessories

10149	Patch cable for gas controller to gas reel only
-------	---





THIS PRODUCT IS **NOT RATED AS INTRINSICALLY SAFE** AND THUS IS **NOT EXPLOSION PROOF**. HATHORN CORPORATION SHALL NOT BE HELD LIABLE FOR ANY DAMAGES, INCLUDING BUT NOT LIMITED TO DIRECT, INDIRECT, SPECIAL, OR CONSEQUENTIAL DAMAGES ARISING OUT OF, RESULTING FROM, OR IN ANY WAY CONNECTED TO THE USE OF THIS PRODUCT IN EXPLOSIVE ENVIRONMENTS. HATHORN ASSUMES NO RESPONSIBILITY FOR OTHER'S USE OR MISUSE OF THIS PRODUCT.



HATHORN

North America: 1-866-HATHORN
 International: +1-905-604-7040
www.hathorncorp.com • info@hathorncorp.com

Camera Heads

PART NUMBER	DESCRIPTION	
10114	1.68" Color Straight View Camera Head Stainless Steel	
10115	1.68" Color Self-Leveling Camera Head Stainless Steel	
10116	1.68" Color Self-Leveling Camera Head Aluminum Stainless Steel	
10132	1.68" Color Straight View Camera Head Aluminum Stainless Steel	
10185	1.43" Color Straight View Camera Head Stainless Steel	
10139	1.43" Color Self-Leveling Camera Head Stainless Steel	
10124	1.23" Color Straight View Camera Head Stainless Steel	
10136	1.23" Color Self-Leveling Camera Head Stainless Steel	
90234	DrainScope, Straight View Camera Head w/assembly, spring, lanyards, sonde	
90393	1" Straight View Camera Head Stainless Steel	
90356	7/8" Straight View Camera Head Stainless Steel	



HATHORN

North America: 1-866-HATHORN
 International: +1-905-604-7040
www.hathorncorp.com • info@hathorncorp.com

Camera Head Skids

PART NUMBER	DESCRIPTION	
10108	P-Trap Skid for 1.68" Camera Heads	
10109	3" Grooved Skid for 1.68" Camera Heads	
10187	P-Trap Skid for 1.43" Straight View Camera Head	
10140	P-Trap Skid for 1.43" Self Leveling Camera Head	
10160	3" Grooved Skid for 1.43" Self Leveling Camera Head	
10123	P-Trap Skid for 1.23" Mini Straight View Camera Head	



HATHORN

North America: 1-866-HATHORN
International: +1-905-604-7040
www.hathorncorp.com • info@hathorncorp.com

Patch Cables









PART NUMBER	DESCRIPTION	
10100	Patch Cable for Optimum & Magnum Systems (Silver/Black)	
10100BB	Patch Cable for Optimum & Magnum Systems (Black/Black)	
10102	Patch Cable for Optimum DVD/DVR Systems (Silver/Silver)	
10149	Patch Cable for Keyhole Gas Camera System (Black/Black)	
10131	Patch Cable for Old Style Sonic (Silver/Silver)	
10173	Patch Cable for Sonic Plus Systems (10 pin black / 7 pin silver)	



HATHORN

North America: 1-866-HATHORN
International: +1-905-604-7040
www.hathorncorp.com • info@hathorncorp.com

Camera Heads





PART NUMBER	DESCRIPTION	
10114	1.68" Color Straight View Camera Head Stainless Steel	
10115	1.68" Color Self-Leveling Camera Head Stainless Steel	
10116	1.68" Color Self-Leveling Camera Head Aluminum Stainless Steel	
10132	1.68" Color Straight View Camera Head Aluminum Stainless Steel	
10185	1.43" Color Straight View Camera Head Stainless Steel	
10139	1.43" Color Self-Leveling Camera Head Stainless Steel	
10124	1.23" Color Straight View Camera Head Stainless Steel	
10136	1.23" Color Self-Leveling Camera Head Stainless Steel	
90234	DrainScope, Straight View Camera Head w/assembly, spring, lanyards, sonde	
90393	1" Straight View Camera Head Stainless Steel	
90356	7/8" Straight View Camera Head Stainless Steel	



HATHORN

North America: 1-866-HATHORN
 International: +1-905-604-7040
www.hathorncorp.com • info@hathorncorp.com

Locators





PART NUMBER	DESCRIPTION	
10130	512Hz Hathorn Locator and Case	 A yellow handheld device with a blue top section and a blue bottom section, connected by a yellow handle. It has a small screen and buttons on the top section.
10150	3-Watt Transmitter	 A yellow rectangular device with a green LCD screen and several buttons. It has a red and black probe connected to the bottom.
10179	Multi Frequency Snap Track Locator	 A white handheld device with a blue top section and a white bottom section, connected by a white handle. It has a small screen and buttons on the top section.
10181	Snap Track 3-Watt Transmitter	 A blue rectangular device with a small screen and several buttons. It has a blue top section and a blue bottom section.



HATHORN

North America: 1-866-HATHORN
International: +1-905-604-7040
www.hathorncorp.com • info@hathorncorp.com

Accessories

PART NUMBER	DESCRIPTION	
10104	12V Power Supply	 A black rectangular power supply unit with a power cord and a connector cable.
10105	Mounting Bracket complete with Pin & Shaft for Large & Extra Large Reels	 A metal mounting bracket with a pin and shaft attached.
90204	Pin for Reel Mounting Bracket	 A metal pin with a ring attached to one end.
10128	Shaft for Controller Mounting Bracket	 A metal shaft with a ring attached to one end.



HATHORN

North America: 1-866-HATHORN
International: +1-905-604-7040
www.hathorncorp.com • info@hathorncorp.com

Accessories

PART NUMBER	DESCRIPTION	
10119	Small Brake Handle for Mini/Mid Reels	
10120	Large Brake Handle for Standard Reel	
10121	Rubber Foot for Reel	
10001232	6" x 1-1/2" Wheel For ACE, ACE2, M2, M7	
10122	8" x 1-3/4" Wheel	



HATHORN

North America: 1-866-HATHORN
International: +1-905-604-7040
www.hathorncorp.com • info@hathorncorp.com